



## ► Series 5400 Calendered Etched Glass Film

Series 5400 is a silver, intermediate, 3-mil (76 micron), calendered vinyl with pressure-sensitive adhesive. It is designed to simulate an etched glass look when applied to various glass surfaces. This cost effective solution is easy to work with, and it provides added elegance to a design. Series 5400 is for indoor and outdoor window applications; the durability is 2 years.

### APPLICATIONS & FEATURES

- Low cost alternative.
- Excellent cutting and weeding.
- Ideal for interior and exterior applications on glass surfaces.

### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
<b>SURFACE FINISH</b>	Gloss Meter 60° Reflection	10%	
<b>THICKNESS</b>	Micrometer, Federal Bench Type	3-mil (76 micron)	
<b>TENSILE STRENGTH</b>	JIS Z 0237	1500 g/10mm	≥ 2.14 kg/cm width
<b>ELONGATION</b>	Instron Tensile Tester as above	≥ 150%	
<b>SHELF LIFE</b>	Free from excessive moisture, temperature, direct sunlight	1 year from factory shipment	
<b>APPLICATION TEMPERATURE RANGE</b>	On clean, dry substrate	60°F to 90°F optimum	10°C to 30°C
<b>HUMIDITY RESISTANCE</b>	Applied to etched aluminum panels 24 hours prior to testing. 100% relative humidity 100° (38°) for 500 hours	51.4 oz/in	0.573 kg/cm
<b>DIMENSIONAL STABILITY</b>	158°F (70°C), 48 hours	0.015 to 0.035 in	0.508 to 0.889 mm
<b>PEEL ADHESION</b>	PSTC-1, 15 min	37 oz/in	0.413 kg/cm
<b>LINER RELEASE</b>	TLMI, 300 in/min (127 cm/min) 2 in (51 mm) wide sample	184 g/2 in	36.2 g/cm





\*Standard Terms & Conditions Apply








## TERMS & CONDITIONS

*The following is made in lieu of all warranties expressed or implied:*

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

August 2014

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA  
EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands  
UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK  
INDIA:  4F1 Court Chambers 35, New Marines Lines, Mumbai 400 020, India

 800 232 7161 / 714 540 2811  800 329 2756  
 +31 70 354 4311  +31 70 355 7721  
 +44 161 884 0592  +31 70 355 7721  
 +91 99 6755 3895

arlon.com